



SAPPHIRE - Listado de Productos Abril 2011



Categoría	Sapphire P/N	Zócalo	Descripción	Memoria	Tipo	Bus	GPU Clock	Memory Clock	Consumo Mínimo	Consumo Máximo	Caja	Cooler y Slot	Cantidad	DVI	VGA	HDMI	HDTV	Display Port	Mini Display Port	Dvi to VGA	Dvi to HDMI	HDMI to DVI	Composite	HDTV Cable	Power Connector	Crossfire Bridge	EAN	Extras	Recycle Packaging
Medio	288L	AGP	HD 4650	1gb	DDR2	128 bits	600 mhz	800 mhz	-	-	Lite Retail	Single Fan	20	2	-	-	1	-	-	1	1	-	1	1	6 pin	-	489 51062 4711 6	-	Si
Entrada	252HDMI	PCI-E	HD 4550	512mb	DDR3	64 bits	600 mhz	1334 mhz	-	-	Lite Retail	Fannless	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 5344 5	Low Profile + Bracket	Si
	291DDR3L	PCI-E	HD 5450	512mb	DDR3	64 bits	650 mhz	1334 mhz	8w	25w	Lite Retail	Fannless	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 5072 7	Low Profile + Bracket	Si
	292DDR3L	PCI-E	HD 5450	1gb	DDR3	64 bits	650 mhz	1334 mhz	8w	25w	Lite Retail	Fannless	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 5047 5	Low Profile + Bracket	Si
Medio	254HDMI	PCI-E	HD 4650	1gb	DDR2	128 bits	600 mhz	800 mhz	-	-	Lite Retail	Single Fan	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 4279 1	-	Si
	296HDMI	PCI-E	HD 4670	1gb	DDR3	128 bits	750 mhz	1600 mhz	-	-	Lite Retail	Single Fan	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 4733 8	-	Si
	293DP	PCI-E	HD 5570	1gb	DDR3	128 bits	650 mhz	1800 mhz	10w	45w	Lite Retail	Single Fan	20	1	1	-	-	1	-	-	-	-	-	-	-	-	489 51062 5103 8	Low Profile + Bracket	Si
	287VGA	PCI-E	HD 5670	512mb	GDDR5	128 bits	775 mhz	4000 mhz	14w	72w	Lite Retail	Dual Fan	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 5050 5	-	Si
	287L	PCI-E	HD 5670	512mb	GDDR5	128 bits	775 mhz	4000 mhz	14w	72w	Lite Retail	Dual Fan	20	1	-	1	-	1	-	1	-	1	-	-	-	-	489 51062 5043 7	-	Si
	289VGA	PCI-E	HD 5670	1gb	DDR3	128 bits	775 mhz	1600 mhz	14w	72w	Lite Retail	Dual Fan	20	1	1	1	-	-	-	-	-	-	-	-	-	-	489 51062 5103 8	-	Si
	289L-2L	PCI-E	HD 5670	1gb	GDDR5	128 bits	775 mhz	3800 mhz	14w	72w	Lite Retail	Dual Fan	20	1	-	1	-	1	-	1	-	1	-	-	-	-	489 51062 5692 7	-	Si
	289FLEX	PCI-E	HD 5670	1gb	GDDR5	128 bits	775 mhz	4000 mhz	14 w	72 w	Lite Retail	Dual Fan	20	2	-	1	-	1	-	1	-	1	-	-	-	-	489 51062 5677 4	Flex Edition	Si
	284L-2L	PCI-E	HD 5750	1gb	GDDR5	128 bits	700 mhz	4600 mhz	16w	86w	Lite Retail	Dual Fan	10	1	-	1	-	1	-	1	-	1	-	-	6 pin	1	489 51062 4877 9	-	Si
Alto	284VXL	PCI-E	HD 5750	1gb	GDDR5	128 bits	710 mhz	4640 mhz	16w	86w	Lite Retail	Dual Fan	10	2	-	1	-	1	-	1	-	-	-	-	6 pin	1	489 51062 5019 2	Vapor-X	Si
	283L-3L	PCI-E	HD 5770	1gb	GDDR5	128 bits	850 mhz	4800 mhz	18w	108w	Lite Retail	Dual Fan	10	2	-	1	-	1	-	1	-	-	-	-	6 pin	1	489 51062 5019 2	-	Si
	283VXL-2L	PCI-E	HD 5770	1gb	GDDR5	128 bits	860 mhz	4800 mhz	18w	108w	Lite Retail	Dual Fan	10	2	-	1	-	1	-	1	-	-	-	-	6 pin	1	489 51062 5058 1	Vapor-X	Si
	283FLEX	PCI-E	HD 5770	1gb	GDDR5	128 bits	850 mhz	4800 mhz	18w	108w	Lite Retail	Dual Fan	10	2	-	1	-	1	-	1	-	1	-	-	6 pin	1	489 51062 5430 5	Flex Edition	Si
	297L	PCI-E	HD5830	1gb	GDDR5	256 bits	800 mhz	4000 mhz	25w	175w	Lite Retail	Dual Fan	10	1	-	1	-	1	-	1	-	-	-	-	2x6 pin	1	489 51062 5816 7	Xtreme	Si
	282extreme	PCI-E	HD5850	1gb	GDDR5	256 bits	725 mhz	4000 mhz	27w	170w	Lite Retail	Dual Fan	10	1	-	1	-	1	-	1	-	-	-	-	2x6 pin	1	489 51062 5818 1	Xtreme	Si
	316L	PCI-E	HD6790	1gb	GDDR5	256 bits	840 mhz	4200 mhz	19w	135w	Lite Retail	Dual Fan	10	2	-	1	-	1	-	1	-	-	-	-	2x6 pin	1	489 51062 5818 1	-	Si
	315L	PCI-E	HD 6850	1gb	GDDR5	256 bits	775 mhz	4000 mhz	19w	127w	Lite Retail	Dual Fan	10	2	-	1	-	1	-	1	-	-	-	-	6 pin	1	489 51062 5579 1	-	Si
	314FLEX	PCI-E	HD 6870	1gb	GDDR5	256 bits	900 mhz	4200 mhz	19w	151w	Lite Retail	Dual Fan	10	2	-	1	-	2	1	-	-	-	-	-	2x6 pin	1	489 51062 5685 9	Flex Edition	Si
	314VXSR	PCI-E	HD 6870	1gb	GDDR5	256 bits	900 mhz	4200 mhz	19w	151w	Full Retail	Dual Fan	10	2	-	1	-	2	1	-	-	-	-	-	2x6 pin	1	489 51062 5661 3	Vapor-X	Si
Extremo	314TXSR	PCI-E	HD 6870	1gb	GDDR5	256 bits	1000 mhz	4400 mhz	19w	151w	Full Retail	Dual Fan	10	2	-	1	-	2	1	-	-	-	-	-	2x6 pin	1	489 51062 5658 3	Toxic	Si
	314-2SR	PCI-E	HD 6870	1gb	GDDR5	256 bits	900 mhz	4200 mhz	19w	151w	Full Retail	Dual Fan	10	2	-	1	-	2	1	-	-	-	-	-	2x6 pin	1	489 51062 5627 9	-	Si
	312SR	PCI-E	HD 6950	2gb	GDDR5	256 bits	800 mhz	5000 mhz	20w	220w	Full Retail	Dual Fan	10	2	-	1	-	2	1	-	-	-	-	2x6 pin	1	489 51062 5689 7	-	Si	
	311-2SR	PCI-E	HD 6970	2gb	GDDR5	256 bits	880 mhz	5500 mhz	20w	250w	Full Retail	Dual Fan	10	2	-	1	-	2	1	-	-	-	-	8+6 pin	1	489 51062 5688 0	-	Si	
	310SR	PCI-E	HD 6990	4gb	GDDR5	2x256	830 mhz	5000 mhz	37w	450w	Full Retail	Dual Fan	10	1+2*	-	1*	-	1*	4	1	-	-	-	-	2x8 pin	1	489 51062 5793 1	-	Si

* con un adaptador

Categoría	Sapphire P/N	Zócalo	Adaptador
Adaptador	-	-	Adaptador DVI a VGA
Adaptador	924	-	Adaptador Display Port a DVI (ATI EyeFinity)
Placa PCI-E 1x	USB3SR	PCI-E	USB 3.0 2-Port I/O PCI-Express Card
Proyector	MP101SR	-	PICO projector